



SINGLE-NEEDLE, SINGLE-THREAD CHAINSTITCH OR TWO-THREAD DOUBLE LOCKED STITCH MACHINE WITH TOP AND BOTTOM FEED FOR USE IN AUTOMATED SYSTEMS



101 SSa-1



401 SSa-1

56100RBTA

Single-needle, single-thread chainstitch machine (101) with top and bottom feed for seaming heavy weight as well as coated bags and simultaneously attaching a binding tape and "Easy-Open" tape (10 mm) from the top. Presser foot with guide for filler cord and one "Easy-Open" tape. Without binding tape folder.

Note: Sewing only in connection with tape resp. filler cord, end-chaining not possible.

56100SABTA

Single-needle, two-thread double locked stitch machine (401) with new improved thread take up, which eliminates thread wrapping around the main shaft.

Note: Sewing without tape, end-chaining possible.

Attention: All machine types will be delivered without thread stand.

| | |
|--------------------------------|--|
| Max. Speed: | 4300 stitches / min. (depending on material and operation) |
| Stitch Range: | 3.6 to 8.5 mm |
| Sewing Capacity: | 6.0 mm |
| Seam Specification 56100RBTA: | 101 SSa-1 |
| Seam Specification 56100SABTA: | 401 SSa-1 |
| Standard Needle: | 143GS200/080 |